



FEATURES

- motor grader or wheel loader applications
- quick hitch, quick coupler or pin-on mountings
- full box section moldboard construction
- push frame is heavy wall, double a-frame tubular construction
- large center pin diameter (3") for long life and less wear

The blade angle is 42 degrees to the ground plane for earth cutting and snow removal applications. The cutting edges are three piece center punched reversible dozer type. Angle Dozer Blades are available in standard duty or severe duty configurations.

SPECIFICATIONS

blade weights*	3000# to 3700# less mountings
blade widths	10' to 13' standard widths
blade height	36" to 42"
moldboard type	smooth rolled, dozer type
moldboard angle to ground plane	42 degrees
moldboard thickness	1/4" standard, 5/16" severe duty
moldboard angle left or right	32 degrees
cutting edges	three section, center with two end bits 3/4" x 8" center punched reversible
hydraulic cylinders and rods	4" x 2" standard, 5" x 2.5" severe duty
center hinge pin diameter	3", greasable
optional	blade mounted skid shoes
optional	moldboard oscillation

*weights are for shipping estimates only and will vary due to options and size variations

WWW.RYLIND.COM

RYLIND INDUSTRIES, INC.
6392 WEST MORRAINE PLACE
LITTLETON, COLORADO 80128

GENERAL SALES OFFICE: 303.979.3548 303.979.4730 FAX