
SRD, SRP SERIES ANGLE DOZER BLADE & PLOW

FOR SMALL LOADERS & MOTOR GRADERS



SRD ANGLE DOZER BLADE AND PLOW



SRP ANGLE DOZER RAMP PLOW (OPTIONAL COUPLER AND SKID SHOES SHOWN)

SPECIFICATIONS

MODELS
WEIGHT
MOLDBOARD
MOLDBOARD LENGTHS AVAILABLE
CUTTING PATH @ 30 DEGREE ANGLE
CENTER HINGE-PIN DIAMETER
ANGLE PUSH FRAME
HYDRAULIC CYLINDERS
ANGLE: CUTTING EDGE TO GROUND PLANE
CUTTING EDGES

MOUNTINGS (ADD APPROXIMATELY 150 LBS.) SKID SHOES

SRD9, SRD10, SRP9, SRP10
1850#, LESS MOUNTINGS
33", 3/16" THICK, SMOOTH ROLLED
9' OR 10'
9' ...96", 10' ...104"
2" GREASEABLE
DOUBLE, TUBULAR A-FRAME DESIGN
3" BORE, 1-1/2" ROD
37 DEGREES (SRD), 17 DEGREES (SRP)
REV. EDGES WITH END BITS (SRD)
HIGHWAY PUNCHED (SRP)
AS SPECIFIED, LOADER OR GRADER
BLADE-MOUNTED, SHIM TYPE (SRD)
MUSHROOM TYPE (SRP)

The SRD blade is a dozer type blade which can be used for snow removal and earth dozing. The SRP blade is a ramp plow type blade with a more vertical cutting edge and a rolled top snow shield. Either blade can be used with down pressure for cutting hard pack snow. Coupler or pin-on mountings are available.